



Product data sheet

HAVSO4T0015G

Characteristics

Variable speed drive, SOLAR, 1.5 kW 380V, 3 phase, HD



Main

Range of product	SOLAR
Product or component type	Variable speed drive
Product specific application	Solar pump
Network number of phases	3 phases
[Us] rated supply voltage	380 V AC - 15...15 % 250...800 V DC
Supply voltage type support	AC/DC
Supply frequency	50...60 Hz
Motor power kW	1.5 kW for heavy duty
Motor power hp	2 hp for heavy duty
Maximum transient current	6.75 A during 1 min (heavy duty) 8.1 A during 3 s (heavy duty) 9 A during 0 s (heavy duty)
Asynchronous motor control profile	Sensorless vector control (SVC) Voltage/frequency ratio (V/f)
Speed drive output frequency	0...400 Hz
Continuous output current	4.5 A

Complementary

Product destination	Asynchronous motors
Function available	MPPT function Auto start-run-stop Energy/flow calculator Pump cleaning Multi-speed operation Energy saving mode
Type of cooling	Fan
Regulation loop	Adjustable PID regulator
Acceleration and deceleration ramps	Linear adjustable separately from 0.01 to 6500 s
Frequency resolution	Analog input: 0.05/50 Hz
Analogue input number	1
Analogue input type	AI1 voltage: 0...10 V AI1 current: 0...20 mA
Discrete input number	4
Discrete input type	Programmable (DI1...DI4)
Analogue output number	1
Analogue output type	AO1 voltage/current: 0...20 mA or 0...10 V
Discrete output number	2

Discrete output type	configurable relay logic 250 V (3 A) for NO relay output circuit configurable relay logic 250 V (3 A) for NC relay output circuit configurable relay logic 30 V DC (3 A) for NO relay output circuit configurable relay logic 30 V DC (3 A) for NC relay output circuit open collector 9...30 V (50 mA)
Output frequency	50 kHz for pulse output at DO1
Display type	5 digits 7 segments for 39 parameters
Device application	Speed control
Type of installation	Indoor/outdoor
Control type	Manual using keypad Using control terminal Using serial port
Device mounting	Wall mounted DIN rail
Speed accuracy	+/- 0.5 % of nominal speed
Protection type	Overcurrent Overvoltage Undervoltage Overheating Overload Short-circuit Phase loss Low light protection
Width	84 mm
Height	152 mm
Depth	148.4 mm
Environment	
Relative humidity	0...95 % without condensation
Ambient air temperature for storage	-20...65 °C
Quality labels	CE
Operating altitude	= 1000 m
IP degree of protection	IP20
Vibration resistance	5.9 m/s²
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Contractual warranty	
Warranty	24 months