

## Product data sheet

## HDB3VR232TC

### Characteristics

### Residual current switch HDB3VR - 2P - 32A - 300mA - for AC



#### Main

Range of product	HDB3VR
Product or component type	Residual current circuit breaker (RCCB)
Poles description	2P
Earth-leakage protection class	Class AC

#### Complementary

[In] rated current	32.0 A
Earth-leakage sensitivity	300.0 mA
Frame size	63AF
[Ue] rated operational voltage	230 V AC
[Ui] rated insulation voltage	500 V
Mechanical durability	2000 cycles
Electrical durability	1000 cycles
Protection type	Earth-leakage protection direct contact
Local signalling	Mechanical indicator for fault
Mounting support	35 mm DIN rail
9 mm pitches	4
Clamping connection capacity	= 25 mm <sup>2</sup>
Tightening torque	2...4.5 N.m
Height	78.5 mm
Width	36.0 mm
Depth	70.0 mm
Embedding depth	43.5 mm
E-commerce address	Residual-current-switch-hdb3vr-ac-type

#### Environment

Environmental characteristic	Fire retardant
Tropicalisation	2
Pollution degree	2
Ambient air temperature for operation	-25...40 °C
Standards	EN/IEC 61008-1

Product certifications

TÜV  
CE  
CB

---

**Offer Sustainability**

---

Sustainable packaging

No

---