

## Product data sheet

## HDB3VR263SC

### Characteristics

### Residual current switch HDB3VR - 2P - 63A - 30mA - for AC



#### Main

Range of product	HDB3VR
Product or component type	Residual current circuit breaker (RCCB)
Poles description	2P
Earth-leakage protection class	Class AC

### Complementary

[In] rated current	63.0 A
Earth-leakage sensitivity	30.0 mA
Frame size	63AF
[Ue] rated operational voltage	230 V AC
[Ui] rated insulation voltage	500 V
Mechanical durability	2000 cycles
Electrical durability	1000 cycles
Protection type	Earth-leakage protection direct contact
Local signalling	Mechanical indicator for fault
Mounting support	35 mm DIN rail
9 mm pitches	4
Clamping connection capacity	= 25 mm <sup>2</sup>
Tightening torque	2...4.5 N.m
Height	3.600 mm
Width	7.850 cm
Depth	7.000 cm
Embedding depth	43.5 mm
Net weight	0.200 kg
E-commerce address	Residual-current-switch-hdb3vr-ac-type

### Environment

Environmental characteristic	Fire retardant
Tropicalisation	2
Pollution degree	2
Ambient air temperature for operation	-25...40 °C

## Product certifications

TÜV  
CE  
CB**Dimensions**

Volume 0.19782 l

**Packing Units**

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 3.600 cm

Package 1 Width 7.850 cm

Package 1 Length 7.000 cm

Package 1 Weight 0.200 kg

**Offer Sustainability**

Sustainable packaging No