# [Himel]

## **Product data sheet**

HDB3VR480SC

Characteristics

Residual current switch HDB3VR - 4P - 80A - 30mA - for AC



#### Main

Range of product	HDB3VR
Product or component type	Residual current circuit breaker (RCCB)
Poles description	4P
Earth-leakage protection class	Class AC

#### Complementary

[In] rated current	80.0 A
Earth-leakage sensitivity	30.0 mA
Frame size	100AF
[Ue] rated operational voltage	400 V AC
[Ui] rated insulation voltage	500 V
Mechanical durability	2000 cycles
Electrical durability	1000 cycles
Protection type	Earth-leakage protection direct contact
Local signalling	Mechanical indicator for fault
Mounting support	35 mm DIN rail
9 mm pitches	8
Clamping connection capacity	= 35 mm <sup>2</sup>
Tightening torque	24.5 N.m
Height	82.5 mm
Width	72.0 mm
Depth	71 mm
Embedding depth	44 mm
E-commerce address	Residual-current-switch-hdb3vr-ac-type

### **Environment**

Environmental characteristic	Fire retardant
Tropicalisation	2
Pollution degree	2
Ambient air temperature for operation	-2540 °C
Standards	EN/IEC 61008-1

Product certifications	TÜV CE CB	
Offer Sustainability		
Sustainable packaging	No	