

## Product data sheet

## HDB3WHN1C40

### Characteristics

Miniature circuit breaker HDB3WH - 18 mm AC - C - 1P - 6 kA - 40 A



### Main

|                           |                           |
|---------------------------|---------------------------|
| Range of product          | HDB3wH                    |
| Product or component type | Miniature circuit-breaker |
| Device application        | Isolation<br>Control      |
| Trip unit technology      | Thermal-magnetic          |
| Suitability for isolation | Yes                       |
| Mechanical durability     | 20000.0 cycles            |
| Electrical durability     | 7000.0 cycles             |

### Complementary

|                                        |                                                        |
|----------------------------------------|--------------------------------------------------------|
| Poles description                      | 1P                                                     |
| [In] rated current                     | 40 A                                                   |
| [Ue] rated operational voltage         | 240 V AC 50/60 Hz                                      |
| Curve code                             | C                                                      |
| Magnetic tripping limit                | 5...10 x In                                            |
| Breaking capacity                      | 6.0 kA                                                 |
| [Ui] rated insulation voltage          | 250.0 V between phase and ground                       |
| [Uimp] rated impulse withstand voltage | 4.0 kV                                                 |
| Cable entry                            | Top<br>Bottom                                          |
| Mounting support                       | 35 mm DIN rail                                         |
| Protection type                        | Overload protection<br>Short-circuit protection        |
| Overvoltage category                   | II                                                     |
| Connections - terminals                | Forked type tag connectors                             |
| Clamping connection capacity           | = 25 mm <sup>2</sup>                                   |
| Tightening torque                      | 2.5 N.m                                                |
| Height                                 | 80 mm                                                  |
| Width                                  | 17.7 mm                                                |
| Depth                                  | 78.5 mm                                                |
| Embedding depth                        | 69.0 mm                                                |
| E-commerce address                     | Hdb3wh-mcb-with-indicator-6ka-breaking-capacity-c-type |

### Environment

|                         |                                         |
|-------------------------|-----------------------------------------|
| Dielectric test voltage | 2.0 kV 50/60 Hz 1 min                   |
| Shock resistance        | 30 gn (duration = 11.0 ms) for 3 shocks |

---

|                                       |                |
|---------------------------------------|----------------|
| Standards                             | EN/IEC 60898-1 |
| IP degree of protection               | IP20           |
| Pollution degree                      | 2              |
| Ambient air temperature for operation | -20...60 °C    |
| Ambient air temperature for storage   | -40...70 °C    |

---

**Offer Sustainability**

---

|                       |    |
|-----------------------|----|
| Sustainable packaging | No |
|-----------------------|----|

---