

Product data sheet

HDB3WL1C40

Characteristics

Miniature circuit breaker HDB3W - 18 mm AC - C - 1P - 4.5 kA - 40 A



Main

| | |
|---------------------------|---------------------------|
| Range of product | HDB3w |
| Product or component type | Miniature circuit-breaker |
| Device application | Isolation Control |
| Poles description | 1P |
| [In] rated current | 40 A |

Complementary

| | |
|--|---|
| [Ue] rated operational voltage | 240 V AC 50/60 Hz |
| Breaking capacity | 4.5 kA |
| Dielectric test voltage | 2.0 kV 50/60 Hz 1 min |
| [Uimp] rated impulse withstand voltage | 4.0 kV |
| Magnetic tripping limit | 5...10 x In |
| Curve code | C |
| [Ui] rated insulation voltage | 250.0 V between phase and ground |
| Suitability for isolation | Yes |
| Mounting support | 35 mm DIN rail |
| Protection type | Overload protection Short-circuit protection |
| Cable entry | Top Bottom |
| Mechanical durability | 25000 cycles |
| Electrical durability | 6000 cycles |
| IP degree of protection | IP20 |
| Overvoltage category | II |
| Provision for padlocking | Handle padlockable in on and off position |
| Connections - terminals | Forked type tag connectors |
| Clamping connection capacity | = 25 mm ² |
| Tightening torque | 3 N.m |
| Height | 80 mm |
| Width | 17.7 mm |
| Depth | 78.5 mm |
| Embedding depth | 61 mm |
| Product weight | 0.091 kg |

Environment

| | |
|---------------------------------------|---|
| Shock resistance | 30 gn (duration = 11.0 ms) for 3 shocks |
| Ambient air temperature for operation | -20...60 °C |
| Trip unit technology | Thermal-magnetic |
| Ambient air temperature for storage | -40...70 °C |
| Operating altitude | 0...2000 m |
| Product certifications | CE CB TÜV |
| Pollution degree | 2 |
| Standards | EN/IEC 60898-1 |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 1.770 cm |
| Package 1 Width | 8 cm |
| Package 1 Length | 7.850 cm |
| Package 1 Weight | 0.091 kg |

Offer Sustainability

| | |
|-----------------------|----|
| Sustainable packaging | No |
|-----------------------|----|