



Product data sheet

HDB3WZ1C20

Characteristics

Miniature circuit breaker, HDB3wZ, 1P, 6 kA, C curve, 20 A, 250 V DC



Main

Range of product	HDB3wZ
Product or component type	Miniature circuit-breaker
Device application	Control Insulation
Poles description	1P

Complementary

[In] rated current	20 A
[Ue] rated operational voltage	250 V DC
Curve code	C
Magnetic tripping limit	6.8...10.2 x In
Breaking capacity	6 kA
[Uimp] rated impulse withstand voltage	6 kV
Mounting support	DIN rail
Protection type	Short-circuit protection Overload protection
Mechanical durability	20000 cycles
Electrical durability	3000 cycles
Connections - terminals	U terminals
Clamping connection capacity	25 mm²
Tightening torque	2.5 N.m
Location of connection	Top or bottom

Environment

Standards	IEC 60947-2
Product certifications	CE CB
IP degree of protection	IP20
Pollution degree	2
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...70 °C
Operating altitude	2000 m

Packing Units

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Unit Type of Package 1	PCE
Number of Units in Package 1	1