




Product data sheet

HDB9Z631B63

Characteristics

Miniature circuit breaker HDB9Z - 18 mm DC - 1P - B curve - 63 A

	Main	
	Range of product	HDB9Z
	Product or component type	Miniature circuit-breaker
	Device application	Isolation Control
	Poles description	1P
	Market segment	Industry Buildings Energy

Complementary

[In] rated current	63 A
Frame size	63AF
[Ue] rated operational voltage	250 V DC
Curve code	B
Magnetic tripping limit	5.5 x In +/- 20 %
Breaking capacity	10 kA at 125 V 6 kA at 250 V
[Uimp] rated impulse withstand voltage	6 kV
Local signalling	Trip indicator
Mounting support	DIN rail
Protection type	Overload protection Short-circuit protection
Mechanical durability	20000 cycles
Electrical durability	10000 cycles
Locking options description	Lock OFF only
Tightening torque	3.5 N.m
Height	71.8 mm
Width	17.7 mm

Environment

Standards	IEC 60947-2
Product certifications	SEMKO CE CB
IP degree of protection	IP20
Pollution degree	2
Tropicalisation	2
Ambient air temperature for operation	-30...70 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ambient air temperature for storage	-40...80 °C
Operating altitude	2000 m