

## Product data sheet

## HDB9Z631B63

### Characteristics

### Miniature circuit breaker HDB9Z - 18 mm DC - 1P - B curve - 63 A



#### Main

Range of product	HDB9Z
Product or component type	Miniature circuit-breaker
Device application	Isolation Control
Poles description	1P
Market segment	Industry Buildings Energy

### Complementary

[In] rated current	63 A
Frame size	63AF
[Ue] rated operational voltage	250 V DC
Curve code	B
Magnetic tripping limit	5.5 x In +/- 20 %
Breaking capacity	10 kA at 125 V 6 kA at 250 V
[Uimp] rated impulse withstand voltage	6 kV
Local signalling	Trip indicator
Mounting support	DIN rail
Protection type	Overload protection Short-circuit protection
Mechanical durability	20000 cycles
Electrical durability	10000 cycles
Locking options description	Lock OFF only
Tightening torque	3.5 N.m
Height	71.8 mm
Width	17.7 mm

### Environment

Standards	IEC 60947-2
Product certifications	SEMKO CE CB
IP degree of protection	IP20
Pollution degree	2
Tropicalisation	2
Ambient air temperature for operation	-30...70 °C

---

Ambient air temperature for storage

-40...80 °C

---

Operating altitude

2000 m

---