Nov 08, 2026

Product data sheet

HDC3225KUE7

Characteristics

Contactor, HDC3-225, 2 NC+2 NO, AC/DC 100-250 V, 50/60 Hz



Main

Range of product	HDC3
Product or component type	Contactor
Poles description	3P
[Ith] conventional free air thermal current	275 A

Complementary

[In] rated current	225 A
[Uc] control circuit voltage	100...250 V AC 50/60 Hz
Auxiliary contact composition	2 NO + 2 NC
[Ui] rated insulation voltage	1000 V
Height	185 mm
Width	120 mm
Depth	161 mm

Environment

Pollution degree	3
Ambient air temperature for operation	-5…40 °C
Average ambient air temperature for operation	= 35 °C (average over 24 hours)
Ambient air temperature for storage	-25…55 °C
Operating altitude	2000 m
Standards	IEC 60947-4-1
Product certifications	CB CE SEMKO
IP degree of protection	IP20
Relative humidity	0…90 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.