



Product data sheet

HDC3S120M7

Characteristics

HDC3S-120 2NO+2NC AC/DC 220/230V 50/60Hz RoHS



Main

Range of product	HDC3S
Product or component type	Contactor
Contactor application	Non-reversing
Poles description	3P
[Ith] conventional free air thermal current	200 A
	200 A
	200 A

Complementary

Utilisation category	AC-3
[Uc] control circuit voltage	220/230 V AC/DC 50/60 Hz
Auxiliary contact composition	2 NO + 2 NC
[Ui] rated insulation voltage	690 V
[Ie] rated operational current	120 A at 220/230 V AC-3
	120 A at 380/400 V AC-3
	86 A at 660/690 V
Motor power kW	37 kW at 220/230 V AC-3
	55 kW at 380/400 V AC-3
	80 kW at 660/690 V AC-3

Environment

Installation category	III
	III
	III
Ambient air temperature for operation	-5...40 °C
	-5...40 °C
	-5...40 °C
Average ambient air temperature for operation	= 35 °C (average over 24 hours)
Ambient air temperature for storage	-25...55 °C
	-25...55 °C
	-25...55 °C
Operating altitude	2000 m
	2000 m
	2000 m
Standards	IEC 60947-4-1
	IEC 60947-4-1
	IEC 60947-4-1
Product certifications	CB
	CE
	SEMKO
IP degree of protection	IP00
	IP00
	IP00
Relative humidity	0...50 % at 0...40 °C
	0...90 % at 0...20 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1