



Product data sheet

HDCAP304000163

Characteristics

Capacitor, HDCAP3, 400 V, 16 kvar, 3 phase, cylindrical



Main

Range of product	HDCAP3
Product or component type	Capacitor
Reactive power rating	13 kvar for 400 V AC 50 Hz 15.6 kvar for 400 V AC 60 Hz
Capacitance tolerance	0...10 %
Dielectric material	Metallized PP film
Impregnation material	Paraffin wax

Complementary

Network rated voltage	400 V
Maximum permissible voltage	1.1 x Un (8 hours over 24 hours)
[Imp] maximum permanent current	1.43 x In
Rated short-duration power frequency withstand voltage	2.15 x Un for 10 s at inter-electrode 3 kV for 10 s between shell and phase
[Ures] residual voltage	50 V after 3 min in case of power failure conforming to IEC 60831
Shape	Cylindrical
Type of installation	Indoor installation
Thread type	16 mm M12
External diameter	86 mm
Height	245 mm

Environment

Operating altitude	2000 m
Ambient air temperature for operation	-25...50 °C
Relative humidity	0...50 % at 40 °C 0...90 % at 20 °C
Standards	IEC 60831

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

Sustainable packaging	No
-----------------------	----