

Product data sheet

HDCX3811BD

Characteristics

HDCX-3811 DC24V RoHS



Main

Range of product	HDCX
Product or component type	Contacteur
Contacteur application	Motor control
Poles description	3P
Mechanical interlocking	Without mechanical interlock

Complementary

Utilisation category	AC-1 AC-2 AC-3 AC-4
[In] rated current	38.0 A
Auxiliary contact composition	1 NO + 1 NC
[Uimp] rated impulse withstand voltage	6 kV
[Ie] rated operational current	38.0 A at 220/230 V AC-3 38.0 A at 380/400 V AC-3 22.0 A at 660/690 V AC-3 14.0 A at 220/230 V AC-4 14.0 A at 380/400 V AC-4 8.9 A at 660/690 V AC-4
Motor power kW	9.0 kW at 220/230 V AC 50/60 Hz AC-3 for 3 phases motors 18.5 kW at 380/400 V AC 50/60 Hz AC-3 18.5 kW at 660/690 V AC 50/60 Hz AC-3 4.0 kW at 220/230 V AC 50/60 Hz AC-4 5.5 kW at 380/400 V AC 50/60 Hz AC-4 6.0 kW at 660/690 V AC 50/60 Hz AC-4
[Ith] conventional free air thermal current	50 A
Height	86.5 mm
Width	45.5 mm
Depth	103 mm
Product weight	0.595 kg

Environment

Installation category	III
Pollution degree	3
Ambient air temperature for operation	-5...40 °C
Average ambient air temperature for operation	= 35 °C (average over 24 hours)
Ambient air temperature for storage	-25...55 °C
Operating altitude	2000 m
Standards	EN/IEC 60947-4-1

Product certifications	CE CB SEMKO
------------------------	-------------------

Relative humidity	0...95 %
-------------------	----------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Offer Sustainability

Sustainable packaging	No
-----------------------	----
