


Product data sheet



HDM2125L1002

Characteristics

Molded case circuit breaker, HDM2-125L, 2P, 100 A, power distribution

	
<b>Main</b>	
Range of product	HDM2
Product or component type	Enclosed moulded case circuit breaker
Poles description	2P
[In] rated current	100 A
Frame size	125AF
<b>Complementary</b>	
[Ue] rated operational voltage	220/240 V 400 V
Network type	AC AC
Network frequency	50/60 Hz
Electrical durability	2000 cycles
Mechanical durability	9000 cycles
[Uimp] rated impulse withstand voltage	8 kV
Suitability for isolation	Yes
Trip unit technology	Thermal-magnetic
Device application	Power distribution protection
[Ics] rated service breaking capacity	30 kA at 220/240 V 20 kA at 400 V
Rated breaking capacity	18 kA at 220/240 V 15 kA at 400 V
Voltage release type	Shunt trip release
Provided equipment	MX voltage release to be ordered separately
[Ui] rated insulation voltage	690 V
Installation category	III
Clamping connection capacity	50 mm²
Height	130 mm
Width	25 mm
Depth	94 mm
Product weight	0.7 kg
<b>Environment</b>	
IP degree of protection	IP20
Pollution degree	3

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Utilisation category	Category A
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-20...70 °C
Operating altitude	0...2000 m
Standards	IEC 60947-2
Product certifications	SEMKO

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.0 cm
Package 1 Width	2.5 cm
Package 1 Length	9.4 cm
Package 1 Weight	700.0 g

Offer Sustainability

Sustainable packaging	No
-----------------------	----