



Product data sheet

HDM2L250S25023CC0

Characteristics

Earth-leakage circuit breaker, HDM2L, 250S, 250 A, 2P, OFF/0.1/0.3A



Main

Range of product	HDM2L
Suitability for isolation	Yes
Trip unit technology	Thermal-magnetic
Device application	Power distribution protection
Earth-leakage sensitivity	100 mA 300 mA

Complementary

Product or component type	Enclosed moulded case circuit breaker with earth leakage protection
Poles description	2P
[In] rated current	250 A
Frame size	250AF
[Ue] rated operational voltage	220/230 V
Network type	AC
Network frequency	50...60 Hz
Electrical durability	4000.0 cycles
Mechanical durability	10000.0 cycles
[Uimp] rated impulse withstand voltage	8.0 kV
[Ics] rated service breaking capacity	21 kA
Rated breaking capacity	35 kA
[Ui] rated insulation voltage	800.0 V
Mounting mode	Fixed front
Clamping connection capacity	120 mm²
Tightening torque	7...10 N.m
Height	165 mm
Width	75 mm
Depth	74 mm

Environment

Ambient air temperature for operation	-5...40 °C
Standards	IEC 60947-2
Product certifications	TÜV CB

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1