Nov 08, 2026

# Product data sheet

# HDM3160F12533XXT

## Characteristics

**Molded case circuit breaker HDM3 - 160F/3P - Mag-therm 125A 50degree**




### Main

| | |
|---|---|
| Range of product | HDM3 |
| Product or component type | Enclosed moulded case circuit breaker |
| Suitability for isolation | Yes |
| Trip unit technology | Thermal-magnetic |
| Device application | Power distribution protection |
| Voltage release type | Shunt trip release<br>Undervoltage release |
| Provided equipment | alarm<br>motor mechanism<br>handle<br>terminal extension<br>interphase barriers<br>MN or MX voltage release |

### Complementary

| | |
|---|---|
| Poles description | 3P |
| [In] rated current | 125.0 A |
| Frame size | 160AF |
| [Ue] rated operational voltage | 400/415 V |
| Network type | AC |
| Network frequency | 50...60 Hz |
| Electrical durability | 4000.0 cycles |
| Mechanical durability | 20000.0 cycles with maintenance<br>10000.0 cycles without maintenance |
| [Uimp] rated impulse withstand voltage | 8.0 kV |
| [Ics] rated service breaking capacity | 30 kA |
| Rated breaking capacity | 50 kA |
| [Ui] rated insulation voltage | 800.0 V |
| Mounting mode | Fixed front |
| Clamping connection capacity | 50 mm² |
| Tightening torque | 9.5…10.5 N.m |
| Utilisation category | Category A |
| Provision for padlocking | Handle padlockable in on and off position |
| Height | 165.0 mm |
| Width | 107.0 mm |
| Depth | 88.0 mm |
| Net weight | 1.53 kg |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

| | |
|---|---|
| IP degree of protection | IP20 |
| Pollution degree | 3 |
| Ambient air temperature for operation | 50.0 °C |
| Ambient air temperature for storage | -20…70 °C |
| Dielectric test voltage | 3 kV |
| Operating altitude | 0...2000 m |
| Standards | IEC 60947-2 |
| Product certifications | CE<br>KEMA |