



Product data sheet

HDM3160S16033XXT

Characteristics

Molded case circuit breaker HDM3 - 160S/3P - Mag-therm 160A 50degree

 Product Image Coming Soon	Main	
	Range of product	HDM3
	Product or component type	Enclosed moulded case circuit breaker
	Suitability for isolation	Yes
	Trip unit technology	Thermal-magnetic
	Device application	Power distribution protection
	Voltage release type	Shunt trip release Undervoltage release
	Provided equipment	alarm motor mechanism handle terminal extension interphase barriers MN or MX voltage release

Complementary

Poles description	3P
[In] rated current	160.0 A
Frame size	160AF
[Ue] rated operational voltage	400/415 V
Network type	AC
Network frequency	50...60 Hz
Electrical durability	4000.0 cycles
Mechanical durability	20000.0 cycles with maintenance 10000.0 cycles without maintenance
[Uimp] rated impulse withstand voltage	8.0 kV
[Ics] rated service breaking capacity	21 kA
Rated breaking capacity	35 kA
[Ui] rated insulation voltage	800.0 V
Mounting mode	Fixed front
Clamping connection capacity	70 mm²
Tightening torque	9.5...10.5 N.m
Utilisation category	Category A
Provision for padlocking	Handle padlockable in on and off position
Height	165.0 mm
Width	107.0 mm
Depth	76.0 mm
Net weight	1.53 kg

Environment

IP degree of protection	IP20
Pollution degree	3
Ambient air temperature for operation	50.0 °C
Ambient air temperature for storage	-20...70 °C
Dielectric test voltage	3 kV
Operating altitude	0...2000 m
Standards	IEC 60947-2
Product certifications	CE KEMA