Nov 25, 2026

Product data sheet

HDM3250MX2A23P

Characteristics

Shunt release, HDM3-160/250, AC 230V, 3P, with terminal, right



Main

Range of product	HDM3
Product or component type	Voltage release
Voltage release type	Shunt release (MX)
Device application	Control
Threshold tripping voltage	0.7...1.1 Un opening

Complementary

[Uc] control circuit voltage	230 V
Network type	AC
Auxiliary connection terminal	Screw terminal, = 1.5 mm²
Frame size	160/250 HDM3 125/250 HDM3E 160/250 HDM3L

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	26.2 cm
Package 1 Width	30.8 cm
Package 1 Length	36 cm
Package 1 Weight	9.5 kg

Offer Sustainability

Sustainable packaging	No

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.