Sep 09, 2026

# Product data sheet

# HDM3630MX2A23P

## Characteristics

**Shunt release, HDM3-400/630, AC 230V, 3P, with terminal, right**

### Main

| | |
|---|---|
| Range of product | HDM3 |
| Product or component type | Voltage release |
| Voltage release type | Shunt release (MX) |
| Device application | Control |
| Threshold tripping voltage | 0.7...1.1 Un opening |

### Complementary

| | |
|---|---|
| [Uc] control circuit voltage | 230 V |
| Network type | AC |
| Auxiliary connection terminal | Screw terminal, = 1.5 mm² |
| Frame size | 400/630 HDM3<br>400/630/800 HDM3E<br>400 HDM3L |

### Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 26.2 cm |
| Package 1 Width | 30.8 cm |
| Package 1 Length | 36 cm |
| Package 1 Weight | 15.33 kg |

### Offer Sustainability

| | |
|---|---|
| Sustainable packaging | No |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.