Nov 08, 2026

Product data sheet

HDM3E16XM16X33XXT

Characteristics

Molded case circuit breaker, HDM3E, 16XM, 3P, electronic, 1600 A, 400 V AC, 50 C



Main

Range of product	HDM3E
Product or component type	Enclosed moulded case circuit breaker
Poles description	3P
[In] rated current	1600 A
Trip unit technology	Electronic

Complementary

[Ue] rated operational voltage	400/415 V
Network type	AC
Network frequency	50/60 Hz
[Ui] rated insulation voltage	1000 V
[Uimp] rated impulse withstand voltage	12 kV
[Icu] ultimate breaking capacity	50 kA
[Ics] rated service breaking capacity	50 kA
[Icw] rated short-time withstand current	42 kA duration: 1 s
Mechanical durability	12500 cycles
Electrical durability	6000 cycles on AC at 400/415 V
Height	327 mm
Width	210 mm
Depth	190 mm

Environment

Product certifications	CE TÜV
Standards	EN/IEC 60947-1 EN/IEC 60947-2
Pollution degree	3
IP degree of protection	IP20
Rated ambient air temperature	50 °C
Ambient air temperature for storage	-40…70 °C
Operating altitude	2000 m
Relative humidity	0…90 %

Packing Units

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

Sustainable packaging	No