



Product data sheet

HDM3E250M25033XXT

Characteristics

Molded case circuit breaker, HDM3E, 250M, 3P, electronic, 250 A, 50 C



Main

Range of product	HDM3E
Product or component type	Enclosed moulded case circuit breaker
Poles description	3P
[In] rated current	250 A
Trip unit technology	Electronic

Complementary

[Ue] rated operational voltage	400/415 V
Network type	AC
Network frequency	50/60 Hz
[Ui] rated insulation voltage	800 V
[Uimp] rated impulse withstand voltage	8 kV
[Icu] ultimate breaking capacity	50 kA
[Ics] rated service breaking capacity	50 kA
[Icw] rated short-time withstand current	2.5 kA duration: 1 s
Mechanical durability	20000 cycles
Electrical durability	8000 cycles on AC at 400/415 V
Height	165 mm
Width	107 mm
Depth	94 mm

Environment

Product certifications	CE TÜV
Standards	EN/IEC 60947-1 EN/IEC 60947-2
Pollution degree	3
IP degree of protection	IP20
Rated ambient air temperature	50 °C
Ambient air temperature for storage	-40...70 °C
Operating altitude	2000 m
Relative humidity	0...90 %

Offer Sustainability

Sustainable packaging	No
-----------------------	----