

Product data sheet

HDM3E630M63033XX

Characteristics

Molded case circuit breaker, HDM3E, 630M, 3P, electronic, 630 A, 40 C



Main

Range of product	HDM3E
Product or component type	Enclosed moulded case circuit breaker
Poles description	3P
[In] rated current	630 A
Trip unit technology	Electronic

Complementary

[Ue] rated operational voltage	400/415 V
Network type	AC
Network frequency	50/60 Hz
[Ui] rated insulation voltage	800 V
[Uimp] rated impulse withstand voltage	8 kV
[Icu] ultimate breaking capacity	50 kA
[Ics] rated service breaking capacity	50 kA
[Icw] rated short-time withstand current	8 kA duration: 1 s
Mechanical durability	10000 cycles
Electrical durability	7500 cycles on AC at 400/415 V
Height	257 mm
Width	150 mm
Depth	107.5 mm

Environment

Product certifications	CE TÜV
Standards	EN/IEC 60947-1 EN/IEC 60947-2
Pollution degree	3
IP degree of protection	IP20
Rated ambient air temperature	40 °C
Ambient air temperature for storage	-40...70 °C
Operating altitude	2000 m
Relative humidity	0...90 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	20 cm
Package 1 Width	11.84 cm
Package 1 Length	47.5 cm
Package 1 Weight	5.92 kg

Offer Sustainability

Sustainable packaging	No
-----------------------	----
