

## Product data sheet

## HDM3E800M80033XX

### Characteristics

Molded case circuit breaker, HDM3E, 800M, 3P, electronic, 800 A, 40 C



### Main

Range of product	HDM3E
Product or component type	Enclosed moulded case circuit breaker
Poles description	3P
[In] rated current	800 A
Trip unit technology	Electronic

### Complementary

[Ue] rated operational voltage	400/415 V
Network type	AC
Network frequency	50/60 Hz
[Ui] rated insulation voltage	1000 V
[Uimp] rated impulse withstand voltage	12 kV
[Icu] ultimate breaking capacity	50 kA
[Ics] rated service breaking capacity	50 kA
[Icw] rated short-time withstand current	10 kA duration: 1 s
Mechanical durability	5000 cycles
Electrical durability	2500 cycles on AC at 400/415 V
Height	280 mm
Width	210 mm
Depth	116 mm

### Environment

Product certifications	CE TÜV
Standards	EN/IEC 60947-1 EN/IEC 60947-2
Pollution degree	3
IP degree of protection	IP20
Rated ambient air temperature	40 °C
Ambient air temperature for storage	-40...70 °C
Operating altitude	2000 m
Relative humidity	0...90 %

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	23 cm
Package 1 Width	9.5 cm
Package 1 Length	37 cm
Package 1 Weight	9.5 kg

**Offer Sustainability**

Sustainable packaging	No
-----------------------	----