



Product data sheet

HDM3S160M06333XXT

Characteristics

Molded case circuit breaker, HDM3S, 160M, 63A 3P, TM, adjustable, 50?

	Main	
	Range of product	HDM3S
	Product or component type	Enclosed moulded case circuit breaker
	Frame size	160AF
	Suitability for isolation	Yes
	Trip unit technology	Thermal-magnetic
	Device application	Power distribution protection
	Voltage release type	Shunt trip release Undervoltage release
	Provided equipment	alarm motor mechanism handle terminal extension interphase barriers MN or MX voltage release

Complementary

Poles description	3P
[In] rated current	63 A
[Ue] rated operational voltage	400/415 V
Network type	AC
Network frequency	50/60 Hz
Electrical durability	1500 cycles
Mechanical durability	8500 cycles
[Uimp] rated impulse withstand voltage	8.0 kV
[Ics] rated service breaking capacity	35 kA at 400 V
Rated breaking capacity	35 kA at 400 V
[Ui] rated insulation voltage	1000 V
Clamping connection capacity	70 mm²
Utilisation category	Category A
Height	155 mm
Width	90 mm
Depth	108 mm

Environment

IP degree of protection	IP20
Installation category	III
Pollution degree	3
Ambient air temperature for operation	-5...50 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ambient air temperature for storage	-20...70 °C
Operating altitude	0...2000 m
Standards	IEC 60947-2
Product certifications	TÜV

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

Sustainable packaging	No
-----------------------	----