Oct 31, 2026

Product data sheet

HDM3SV250F25033N

Characteristics

Molded Case Circuit Breaker HDM3SV-250F 36kA 250A 3P 0.7-1/5-10 40?



Main

Range of product	HDM3SV
Product or component type	Enclosed moulded case circuit breaker
Suitability for isolation	Yes
Trip unit technology	Thermal-magnetic
Device application	Power distribution protection

Complementary

Poles description	3P
Frame size	250AF
[Ue] rated operational voltage	400/415 V
Network type	AC
Network frequency	50...60 Hz
[Uimp] rated impulse withstand voltage	8.0 kV
Mounting mode	Fixed front
Clamping connection capacity	120 mm²
Tightening torque	9.5…10.5 N.m
Utilisation category	Category A
Provision for padlocking	Handle padlockable in on and off position
Height	165 mm
Width	105 mm
Depth	97 mm
Net weight	1.86 kg

Environment

IP degree of protection	IP30
Installation category	III
Pollution degree	3
Operating altitude	0...2000 m
Standards	EN/IEC 60947-2 SANS 60947-2

Packing Units

Unit Type of Package 1	PCE

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Number of Units in Package 1	1
Package 1 Height	26.2 cm
Package 1 Width	35.2 cm
Package 1 Length	35.4 cm
Package 1 Weight	1.80666666666667 kg

Offer Sustainability

Sustainable packaging	No