Sep 09, 2026

Product data sheet

HDPZ50PR24NF

Characteristics

Distribution box, HDPZ50P, full plastic, 24 ways, flush mounted, ABS

Main

Range of product	HDPZ50
Device application	Low voltage electrical distribution
Product or component type	Empty consumer unit
Enclosure type	Insulated enclosure
Number of 18 mm modules per row	24.0
Provided equipment	Earth/neutral terminal block
Type of front cover	Transparent

Complementary

Enclosure mounting	Flush
Number of horizontal rows	2.0
Number of ways	24 ways
Enclosure material	Plastic
[In] rated current	100 A
[Ue] rated operational voltage	230/240 V
Type of rail	DIN
Cable entry	Knock-out
Downside connection	Rear
Comb busbar and distribution block compatibility	YES
Height	310.5 mm
Width	261 mm
Depth	74.5 mm

Environment

Standards	IEC 60670
IP degree of protection	IP30
Ambient air temperature for operation	-5…60 °C

Offer Sustainability

Sustainable packaging	No

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.