



Product data sheet

HDQ1S320033200GU

Characteristics

HDQ1S 3200AF 3P 3200A G Type Top



Product Image Coming Soon

Main

Range of product	HDQ1S
Device application	Change source of supply
Product or component type	Transfer switch
Poles description	3P
Network type	AC
Network frequency	50/60 Hz
Mounting mode	Fixed
Upside connection	Screwed
Downside connection	Screwed
Contact position indicator	Yes
[Icm] rated short-circuit making capacity	105 kA 400/415 V AC at 50/60 Hz

Complementary

Display type	LED
Transfer switch class	PC
Utilisation category	AC-32B AC-33iB AC-33B
Mounting support	Plate
[Ui] rated insulation voltage	1000.0 V
[Uimp] rated impulse withstand voltage	12.0 kV
Suitability for isolation	Yes
Mechanical durability	2000 cycles
Electrical durability	500 cycles
Height	440.0 mm
Width	785.0 mm
Depth	560.0 mm
Product weight	90.40 kg

Environment

Standards	IEC 60947-6-1
Product certifications	CCC CE CB

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	44 cm
Package 1 Width	78.5 cm
Package 1 Length	56 cm
Package 1 Weight	90.40 kg

Offer Sustainability

Sustainable packaging	No
-----------------------	----