




Product data sheet

HDQ3S008020032P

Characteristics

Transfer switch equipment, HDQ3S, 80AF/2P, 32A, power to power

	Main	
	Range of product	HDQ3S
	Device application	Change source of supply
	Product or component type	Transfer switch
	Poles description	2P
	Network type	AC
	Network frequency	50/60 Hz
	Mounting mode	Fixed
	Upside connection	Screwed
	Downside connection	Screwed
	Contact position indicator	Yes
	[Icm] rated short-circuit making capacity	7.65 kA 230 V AC at 50/60 Hz

Complementary

Transfer switch class	PC
Number of contact position	3
Utilisation category	AC-33B AC-33iB AC-32B
Control type	Integrated controller
Mounting support	Plate
Suitability for isolation	Yes
Mechanical durability	8000.0 cycles
Electrical durability	2000.0 cycles
Height	245.0 mm
Width	120.0 mm
Depth	100.0 mm
Net weight	2.76 kg

Environment

Standards	IEC 60947-6-1 GB 14048.11
IP degree of protection	IP30

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Package 1 Height	24.5 cm
Package 1 Width	12 cm
Package 1 Length	10 cm
Package 1 Weight	2.76 kg