



Product data sheet

HDQ3S008020063P

Characteristics

Transfer switch equipment, HDQ3S, 80AF/2P, 63A, power to power



Main

Range of product	HDQ3S
Device application	Change source of supply
Product or component type	Transfer switch
Poles description	2P
Network type	AC
Network frequency	50/60 Hz
Mounting mode	Fixed
Upside connection	Screwed
Downside connection	Screwed
Contact position indicator	Yes
[Icm] rated short-circuit making capacity	7.65 kA 230 V AC at 50/60 Hz

Complementary

Transfer switch class	PC
Number of contact position	3
Utilisation category	AC-33B AC-33iB AC-32B
Control type	Integrated controller
Mounting support	Plate
Suitability for isolation	Yes
Mechanical durability	8000.0 cycles
Electrical durability	2000.0 cycles
Height	245.0 mm
Width	120.0 mm
Depth	100.0 mm
Product weight	2.76 kg

Environment

Standards	IEC 60947-6-1 GB 14048.11
IP degree of protection	IP30

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Height	24.5 cm
Package 1 Width	12 cm
Package 1 Length	10 cm
Package 1 Weight	2.76 kg

Offer Sustainability

Sustainable packaging	No
-----------------------	----
