

Product data sheet

HDR3S9370

Characteristics

Thermal overload relay, HDR3s-93, 55..70 A



Main

Range of product	HDR3s
Product or component type	Thermal overload relay
Device application	Motor protection
Thermal protection adjustment range	55...70 A
Frame size	93A

Complementary

Protection type	Overload Phase failure
Reset	Automatic reset Manual reset
Control type	Test button Stop button
[I _{th}] conventional free air thermal current	5 A
Local signalling	Trip indicator
[I _e] rated operational current	1.57 A at 230 V AC-15 0.9 A at 400 V AC-15 0.14 A at 230 V DC-13
[U _i] rated insulation voltage	660 V
[U _{imp}] rated impulse withstand voltage	6 kV
Utilisation category	AC-15 DC-13
Poles description	3P
Height	83 mm
Width	72 mm
Depth	119 mm

Environment

Installation category	III
Pollution degree	3
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-25...55 °C
Operating altitude	2000 m
Standards	IEC 60947-4-1

Product certifications	CB CE SEMKO
------------------------	-------------------

IP degree of protection	IP20
Relative humidity	0...95 %

Offer Sustainability

Sustainable packaging	No
-----------------------	----
