

Product data sheet

HDS338B12Q710

Characteristics

Magnetic starter, HDS3-38, 10 A, 380/400 V, 50/60 Hz, plastic



Main

Range of product	HDS3
Product or component type	Enclosed DOL starter
Device application	Motor control Motor protection
Device composition	HDC3 contactor HDR3s thermal overload relay
Thermal protection adjustment range	7...10 A
Motor power hp	3.0 hp at 240 V AC 50/60 Hz 5.5 hp at 380/400 V AC 50/60 Hz 5.5 hp at 440 V AC 50/60 Hz 7.5 hp at 660/690 V AC 50/60 Hz
Motor power kW	2.2 kW at 240 V AC 50/60 Hz 4.0 kW at 380/400 V AC 4.0 kW at 440 V AC 5.5 kW at 660/690 V AC

Complementary

Housing material	Plastic
Utilisation category	AC-3
[Uc] control circuit voltage	380/400 V AC 50/60 Hz
Control type	Push-button start green I Push-button stop/reset red O
Width	115 mm
Height	203 mm
Depth	129 mm

Environment

IP degree of protection	IP54
Standards	IEC 60947-4-1
Quality labels	CE
Ambient air temperature for operation	-5...40 °C

Offer Sustainability

Sustainable packaging	No
-----------------------	----