




Product data sheet

HDW316M104FHNNN4M

Characteristics

Air circuit breaker, HDW3, 1600AF, 1000 A, 4P, fixed horizontal, 4 NO + 4 NC

	Main	
	Range of product	HDW3
	Product or component type	Air circuit breaker
	Frame size	1600AF
	[Icu] ultimate breaking capacity	35 kA at 690 V load 50 kA at 400 V load
	[Ics] rated service breaking capacity	35 kA at 690 V 42 kA at 400 V
	[Icw] rated short-time withstand current	35 kA at 690 V duration: 1 s 42 kA at 400 V duration: 1 s

Complementary

[In] rated current	1000 A
Poles description	4P
Mounting mode	Fixed
Mounting position	Horizontal
[Uc] control circuit voltage	230 V AC: motor mechanism (MCH) + closing release (XF) 230 V AC: shunt release (MX) 230 V AC: undervoltage release (MN)
Maximum tripping time	25 ms
Maximum closing response time	70 ms
Auxiliary contact composition	4 NO + 4 NC
Product compatibility	Series intelligent controller iTR326A standard protection
Height	310 mm
Width	346 mm
Depth	229 mm
Net weight	17 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	31.0 cm
Package 1 Width	34.6 cm
Package 1 Length	22.9 cm
Package 1 Weight	17.0 kg

Offer Sustainability

Sustainable packaging	No
-----------------------	----

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.