

Product data sheet

HDW320M163DHNN56H

Characteristics

Air circuit breaker, HDW3, 2000AF, 1600 A, 3P, drawout horizontal, 6 NO + 6 NC



Main

Range of product	HDW3
Product or component type	Air circuit breaker
Frame size	2000AF
[Icu] ultimate breaking capacity	50 kA at 690 V load 80 kA at 400 V load
[Ics] rated service breaking capacity	40 kA at 690 V 65 kA at 400 V
[Icw] rated short-time withstand current	40 kA at 690 V duration: 1 s 65 kA at 400 V duration: 1 s

Complementary

[In] rated current	1600 A
Poles description	3P
Mounting mode	Drawout
Mounting position	Horizontal
[Uc] Control circuit voltage	230 V AC: motor mechanism (MCH) + closing release (XF) 230 V AC: shunt release (MX)
Voltage release type	Without undervoltage release
Maximum tripping time	25 ms
Maximum closing response time	70 ms
Auxiliary contact composition	6 NO + 6 NC
Product compatibility	Series intelligent controller iTR326H advance protection
Height	436 mm
Width	405 mm
Depth	425 mm
Product weight	73.8 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	55 cm
Package 1 Width	45.5 cm
Package 1 Length	54.5 cm
Package 1 Weight	64 kg

Offer Sustainability

