



Product data sheet

HDW332S323FH55N6

Characteristics

Air circuit breaker, HDW3, 3200AF, 3200 A, 3P, fixed horizontal, 6 NO + 6 NC



Product Image Coming Soon

Main

Range of product	HDW3
Product or component type	Air circuit breaker
Frame size	3200AF
[Icu] ultimate breaking capacity	65 kA at 400 V load 50 kA at 690 V load
[Ics] rated service breaking capacity	65 kA at 400 V 50 kA at 690 V
[Icw] rated short-time withstand current	65 kA at 400 V duration: 1 s 50 kA at 690 V duration: 1 s

Complementary

[In] rated current	3200 A
Poles description	3P
Mounting mode	Fixed
Mounting position	Horizontal
[Uc] control circuit voltage	230 V AC: undervoltage release (MN)
Voltage release type	Without motor mechanism, closing release and shunt release
Maximum tripping time	25 ms
Maximum closing response time	70 ms
Auxiliary contact composition	6 NO + 6 NC
Product compatibility	Without intelligent controller
Height	397 mm
Width	428 mm
Depth	327 mm
Product weight	53.4 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	39.7 cm
Package 1 Width	42.8 cm
Package 1 Length	32.7 cm
Package 1 Weight	53.4 kg