





Product data sheet

HJKF5CV12Z

Characteristics

Intelligent reactive power compensation controller, HJKF5C, 400V, 12 steps, AC, RS485



Main

Range of product	HJKF
Product or component type	Power factor controller
Metering type	Power factor
Provided equipment	User manual

Complementary

Number of step output contacts	12
[Us] rated supply voltage	400 V AC 50...60 Hz
Operating mode	Manual or automatic
Device connection	Connection to remote switch protocol: RS485 interface: 2-wire RS 485
Input function	1 x with analogue input Current and voltage signal: 1 x with analogue input
Type of measurement	Cos ?
Information displayed	Number of switching cycles per step
Type of alarms	Abnormal cos ?
Input type	With analogue input
Output type	Control contactor: 400 V AC 50/60 Hz
Settings operating mode	Manual
Type of setting	Choice of stepping programs: fixed
Mounting support	Panel

Environment

IP degree of protection	IP30
Operating altitude	= 2000 m
Ambient air temperature for operation	-25...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

Sustainable packaging	No
-----------------------	----

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.