



Product data sheet

HJX21204C7

Characteristics

Contactor, HJX2-12, 4P, 4NO, 36 V, 50/60 Hz



Main

Range of product	HJX2 4P
Product or component type	Contactor
Contactor application	Non-reversing
Poles description	4P
[Uc] control circuit voltage	36 V AC 50/60 Hz
Mechanical interlocking	Without mechanical interlock

Complementary

[In] rated current	12 A
Auxiliary contact composition	4 NO
[Ui] rated insulation voltage	690 V
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	12 A at 380/400 V AC-3 8.9 A at 660/690 V AC-3 5 A at 380/400 V AC-4 2 A at 660/690 V AC-4
Motor power kW	5.5 kW at 380/400 V AC 50/60 Hz AC-3 for 3 phases motors 7.5 kW at 660/690 V AC 50/60 Hz AC-3 2.2 kW at 380/400 V AC 50/60 Hz AC-4 1.5 kW at 660/690 V AC 50/60 Hz AC-4
[Ith] conventional free air thermal current	25 A

Environment

Installation category	III
Pollution degree	3
Ambient air temperature for operation	-5...40 °C
Average ambient air temperature for operation	= 35 °C (average over 24 hours)
Ambient air temperature for storage	-25...55 °C
Operating altitude	2000 m
Standards	EN/IEC 60947-4-1
Product certifications	SEMKO
IP degree of protection	IP20
Relative humidity	0...90 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

