

Product data sheet

HLAY5BA65

Characteristics

Push-button, HLAY5, flush, 1 NO + 1 NC, blue



Main

Range of product	HLAY5
Device presentation	Complete product
Product or component type	Push-button
Bezel material	Metal
Mounting diameter	22 mm
Head type	Standard

Complementary

Cap/operator or lens colour	Blue
Fixing collar material	Metal
Shape of signaling unit head	Round
Type of operator	Spring return
Operator profile	Blue flush
Contacts type and composition	1 NO + 1 NC
Contact operation	Slow-break
Contacts usage	Standard contacts
Mechanical durability	1000000 cycles
Connections - terminals	Screw clamp terminals
[Ith] conventional free air thermal current	6 A
[Uimp] rated impulse withstand voltage	6 kV
[Ie] rated operational current	2 A at 380 V 3.3 A at 220 V, AC-15 0.5 A at 220 V 1.1 A at 110 V, DC-13
Electrical durability	1000000 cycles AC 200000 cycles DC
E-commerce address	Hlay5-pushbuttons-mushroom-and-emergency-stop-pushbuttons-1

Environment

Ambient air temperature for operation	-5...40 °C
IP degree of protection	IP40 IP65 with protective cover
Standards	IEC 60947-5-1

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Offer Sustainability

Sustainable packaging

No
