

## Product data sheet

## HLAY5BG25

### Characteristics

Key switch, HLAY5, 1 NO + 1 NC, 2 positions 45°, stay put, black



### Main

Range of product	HLAY5
Device presentation	Complete product
Product or component type	Key switch
Bezel material	Metal
Mounting diameter	22 mm
Head type	Standard

### Complementary

Fixing collar material	Metal
Cap/operator or lens colour	Black
Shape of signaling unit head	Round
Type of operator	Stay put
Operator profile	Key switch
Operator position information	2 positions 45°
Key withdrawal position	Center
Contacts type and composition	1 NO + 1 NC
Contact operation	Slow-break
Contacts usage	Standard contacts
Mechanical durability	100000 cycles
Connections - terminals	Screw clamp terminals
[Ith] conventional free air thermal current	6 A
[Uimp] rated impulse withstand voltage	6 kV
[Ie] rated operational current	2 A at 380 V 3.3 A at 220 V, AC-15 0.5 A at 220 V 1.1 A at 110 V, DC-13
Electrical durability	50000 cycles
E-commerce address	Hlay5-selector-switches-with-handle

### Environment

Ambient air temperature for operation	-5...40 °C
Standards	IEC 60947-5-1

### Packing Units

Unit Type of Package 1	PCE
------------------------	-----

---

**Offer Sustainability**

---

Sustainable packaging

No

---