



Product data sheet

HLD1122C41M5

CharacteristicsMonolithic pilot light, HLD11, 220 V AC, full cover head, short terminal, capacitance type, yellow



Main

|                           |                    |
|---------------------------|--------------------|
| Range of product          | HLD11              |
| Device presentation       | Monolithic product |
| Product or component type | Pilot light        |
| Head type                 | Full-cover head    |
| Load type                 | Capacitive         |
| Bezel material            | Plastic            |
| Mounting diameter         | 22 mm              |

Complementary

|                              |                       |
|------------------------------|-----------------------|
| [Us] rated supply voltage    | 220 V AC              |
| Shape of signaling unit head | Round                 |
| Shape                        | Short                 |
| Cap/operator or lens colour  | Yellow                |
| Connections - terminals      | Screw clamp terminals |
| Service life in hours        | 30000 h               |
| E-commerce address           | Hld11                 |

Environment

|                         |               |
|-------------------------|---------------|
| Standards               | IEC 60947-5-1 |
| IP degree of protection | IP65          |

Packing Units

|                              |     |
|------------------------------|-----|
| Unit Type of Package 1       | PCE |
| Number of Units in Package 1 | 1   |

Offer Sustainability

|                       |    |
|-----------------------|----|
| Sustainable packaging | No |
|-----------------------|----|