

## Product data sheet

### HSJW30GE

Voltage stabilizer, HSJW, servo motor type, 30 kVA, cabinet shape, LED display, 260...430 V input, 380 V output

#### Characteristics



Product Image Coming Soon

#### Main

Range of product	HSJW
Product or component type	Voltage stabilizer
Technology type	Servo motor
Provided equipment	User manual

#### Complementary

Rated power in VA	30 kVA
Minimum insulating resistance	5 MOhm
Maximum [In] rated current	45.6 A
Efficiency	92 %
Input voltage limits	260...430 V
Optional feature	Bypass Cooling fan
Protection type	Overvoltage for output Undervoltage protection optional for input Undervoltage protection optional for output Overload protection optional Phase failure optional Temperature rise protection optional Time delay optional Inrush surge protection optional
Signalling function	LED
Output voltage	380 V AC +/- 4 %
Network frequency	50/60 Hz
[Uimp] rated impulse withstand voltage	1.5 kV per minute
Mounting support	Floor-standing

#### Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...90 %
Operating altitude	0...2000 m
Standards	EN 61000-6-2 EN 61000-6-4 EN 61558-1
Product certifications	CE

#### Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

**Offer Sustainability**

---

Sustainable packaging	No
-----------------------	----

---