

## Product data sheet

### HSVCB5CI85

Voltage stabilizer, HSVC, wall-mounted servo motor type, 5 kVA, LCD display, 85...250 V input, 220 V output

#### Characteristics



#### Main

|                           |                    |
|---------------------------|--------------------|
| Range of product          | HSVC               |
| Product or component type | Voltage stabilizer |
| Technology type           | Servo motor        |
| Provided equipment        | User manual        |

#### Complementary

|                            |  |
|----------------------------|--|
| Rated power in VA          | 5 kVA  |
| Maximum [In] rated current | 22.7 A   |
| Efficiency                 | 92 %   |
| Input voltage limits       | 85...250 V   |
| Optional feature           | Cooling fan  |
| Function available         | Integrated bypass  |
| Protection type            | Overvoltage for output<br>Undervoltage protection for output<br>Overload protection<br>Temperature rise protection<br>Time delay |
| Display type               | LCD  |
| Output voltage             | 220 V AC +/- 4 %   |
| Network frequency          | 50/60 Hz   |
| Mounting support           | Wall mounted   |

#### Environment

|                                       |  |
|---------------------------------------|--|
| Ambient air temperature for operation | -5...40 °C                                 |
| Relative humidity                     | 0...90 %                                   |
| Operating altitude                    | 0...2000 m                                 |
| Standards                             | EN 61000-6-2<br>EN 61000-6-4<br>EN 61558-1 |

#### Offer Sustainability

|                       |    |
|-----------------------|----|
| Sustainable packaging | No |
|-----------------------|----|