



Product data sheet

HTND15GH230WF

Characteristics

Voltage stabilizer, HTND, 15 kVA, cabinet terminal, connect, 230 V output, with 2 fans



Product Image Coming Soon

Main

| | |
|---------------------------|--------------------|
| Range of product | HTND |
| Product or component type | Voltage stabilizer |
| Technology type | Servo motor |
| Rated power in VA | 15 kVA |
| Provided equipment | User manual |
| Output voltage | 230 V |

Complementary

| | |
|----------------------|------------------------------|
| Response time | 1 s |
| Efficiency | 92 % |
| Input voltage limits | 140...250 V |
| Type of cooling | 2.0 fan |
| Protection type | Overvoltage Short-circuit |
| Network frequency | 50/60 Hz |
| Mounting mode | Cabinet mount |

Environment

| | |
|---------------------------------------|--|
| Ambient air temperature for operation | -5...40 °C |
| Relative humidity | 0...90 % |
| Humidity storage | 0...90 % |
| Operating altitude | 0...2000 m |
| Storage altitude | 0...2000 m |
| Standards | EN 61000-6-2 EN 61000-6-4 EN 61558-1 |
| Product certifications | CE |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 79 cm |
| Package 1 Width | 44.5 cm |
| Package 1 Length | 42.5 cm |
| Package 1 Weight | 67 kg |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.