



Product data sheet

HWDF1G1W

Characteristics

Switch, Flexo Series, 16 AX, 250 V, 1 gang, 1-way, white

	Main	
	Range of product	FLEXO
	Product or component type	Switch
	Device presentation	Complete mechanism
	Device mounting	Flush
	Number of gangs	1 gang
	Device application	Lighting
	Colour tint	White

Complementary

Switch function	1-way
Rated current	16 AX
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50 Hz
Number of modules	1 module
Actuator	Rocker
Material	PC (polycarbonate)
Contacts material	Copper
Connections - terminals	Screw terminals
Type of installation	Indoor
Fixing center	60 mm +/- 0.3 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
IP degree of protection	IP20
Standards	CE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty	120 months
----------	------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.