




Product data sheet

HWDPLD3

Characteristics

Dimmer, Prime V2 Series, light, 300 W, white

	Main	
	Range of product	Prime V2 Series
	Product or component type	Dimmer
	Device presentation	Complete mechanism
	Device mounting	Flush
	Device application	Light control
	Colour tint	White

Complementary

Power range	0...300 W
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50 Hz
Number of modules	1 module
Material	PC (polycarbonate)
Actuator	Rotary
Connections - terminals	Screw terminals
Type of installation	Indoor
Fixing center	60 mm +/- 0.3 mm
Width	86 mm
Height	86 mm
E-commerce address	Prime-series-dimmer

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
IP degree of protection	IP20
Standards	IEC 60669-2

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty	12 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

