Apr 03, 2026

Product data sheet

H96TA1000WG

Characteristics

Panel meter, H96, amperemeter 1000 A

Main

Range of product	H96
Product or component type	Ammeter

Complementary

Market segment	Panel builder
Type of measurement	Current
Network frequency	50 Hz
[In] rated current	1000 A
Network number of phases	1 phase
Signalling function	Dial pointer indication
Measurement current	5 A
Accuracy class	Class 1.5
Response time	= 4 s
Mounting mode	Flush-mounted
Type of installation	Indoor installation
Mounting position	Vertical
Detection angle	90°
Width	96 mm
Height	96 mm

Environment

IP degree of protection	IP42
Ambient air temperature for operation	-10…45 °C
Ambient air temperature for storage	-25…55 °C
Relative humidity	25…80 %
Operating altitude	0...2000 m
Standards	IEC 60051

Packing Units

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

Sustainable packaging	No