Nov 10, 2026

# Product data sheet

# HDB3LE4C10

## Characteristics

**Residual Current Operated Circuit Breaker, HDB3LE, 4P, C curve, 10A, 30mA, AC**



### Main

| | |
|---|---|
| Range of product | HDB3LE |
| Product or component type | Residual current breaker with overcurrent protection (RCBO) |
| Mechanical durability | 20000 cycles |
| [In] rated current | 10 A |
| Electrical durability | 10000 cycles |
| Trip unit technology | Thermal-magnetic |
| Device application | Isolation |

### Complementary

| | |
|---|---|
| Poles description | 4P |
| [In] rated current | 10 A |
| Earth-leakage sensitivity | 30.0 mA |
| [Ue] rated operational voltage | 400 V AC 50...60 Hz |
| Residual current | 30 mA |
| [Uimp] rated impulse withstand voltage | 4.0 kV |
| Curve code | C |
| Magnetic tripping limit | 5...10 x In |
| Breaking capacity | 6 kA |
| [Ui] rated insulation voltage | 500 V |
| Cable entry | Top and bottom |
| Mounting support | 35 mm DIN rail |
| Clamping connection capacity | = 25 mm² |
| Tightening torque | 2.5…4.5 N.m |
| Connections - terminals | Forked type tag connectors |

### Environment

| | |
|---|---|
| Tropicalisation | 2 |
| IP degree of protection | IP20 |
| Electrical shock protection class | Class II |
| Ambient air temperature for operation | -35…70 °C |
| Standards | IEC 61009-1 |
| Product certifications | CE |

### Packing Units

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |

## Offer Sustainability

| | |
|---|---|
| Sustainable packaging | No |

## Contractual warranty