



Product data sheet

HDB3LTH1C10R30

Characteristics

Residual current device, HDB3LT, 10kA, 1P+N, C, 10A, 30mA



Main

Range of product	HDB3LT
Product or component type	Residual current device
Mechanical durability	20000 cycles
[In] rated current	10 A
Electrical durability	10000 cycles
Trip unit technology	Thermal-magnetic
Device application	Isolation

Complementary

Poles description	1P + N
[In] rated current	10 A
Earth-leakage sensitivity	30 mA
[Ue] rated operational voltage	230/240 V AC 50...60 Hz
Residual current	10 mA
[Uimp] rated impulse withstand voltage	4 kV
Curve code	C
Magnetic tripping limit	5...10 x In
Cable entry	Top
Mounting support	35 mm DIN rail
Clamping connection capacity	= 25 mm ²
Tightening torque	2 N.m
Connections - terminals	Forked type tag connectors

Environment

Tropicalisation	2
IP degree of protection	IP20
Pollution degree	Level 2
Ambient air temperature for operation	-20...60 °C
Ambient air temperature for storage	-40...70 °C
Standards	IEC 61009-1
Product certifications	CE

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Number of Units in Package 1	1
------------------------------	---

Contractual warranty

Warranty	18 months
----------	-----------