Nov 10, 2026

# Product data sheet

# HDB3WL4C25

## Characteristics

**Miniature circuit breaker HDB3W - 18 mm AC - C - 4P - 4.5 kA - 25 A**




### Main

| | |
|---|---|
| Range of product | HDB3w |
| Product or component type | Miniature circuit-breaker |
| Device application | Isolation<br>Control |
| Poles description | 4P |
| [In] rated current | 25 A |

### Complementary

| | |
|---|---|
| [Ue] rated operational voltage | 415 V AC 50/60 Hz |
| Breaking capacity | 4.5 kA |
| Dielectric test voltage | 2.0 kV 50/60 Hz 1 min |
| [Uimp] rated impulse withstand voltage | 4.0 kV |
| Magnetic tripping limit | 5...10 x In |
| Curve code | C |
| [Ui] rated insulation voltage | 250.0 V between phase and ground<br>500.0 V between phases |
| Suitability for isolation | Yes |
| Mounting support | 35 mm DIN rail |
| Protection type | Overload protection<br>Short-circuit protection |
| Cable entry | Top<br>Bottom |
| Mechanical durability | 25000 cycles |
| Electrical durability | 6000 cycles |
| IP degree of protection | IP20 |
| Overvoltage category | II |
| Provision for padlocking | Handle padlockable in on and off position |
| Connections - terminals | Forked type tag connectors |
| Clamping connection capacity | = 25 mm² |
| Tightening torque | 3 N.m |
| Height | 80 mm |
| Width | 70.8 mm |
| Depth | 78.5 mm |
| Embedding depth | 61 mm |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

| | |
|---|---|
| Shock resistance | 30 gn (duration = 11.0 ms) for 3 shocks |
| Ambient air temperature for operation | -20…60 °C |
| Trip unit technology | Thermal-magnetic |
| Ambient air temperature for storage | -40…70 °C |
| Operating altitude | 0...2000 m |
| Product certifications | CE<br>CB<br>TÜV |
| Pollution degree | 2 |
| Standards | EN/IEC 60898-1 |

## Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 25 cm |
| Package 1 Width | 24.5 cm |
| Package 1 Length | 35.5 cm |
| Package 1 Weight | 12.73 kg |

## Offer Sustainability

| | |
|---|---|
| Sustainable packaging | No |