



Product data sheet

HDRX38P63

Characteristics

HDRX-38 0.4-0.63A RoHS



Main

Range of product	HDRX
Product or component type	Thermal overload relay
Device application	Motor protection
Thermal protection adjustment range	0.4...0.63 A
Frame size	38A

Complementary

Protection type	Overload Phase failure
Reset	Automatic reset Manual reset
Control type	Test button Stop button
Local signalling	Trip indicator
[Ie] rated operational current	1.64 A at 220/230 V AC-15 0.95 A at 380/400 V AC-15 0.15 A at 220/230 V DC-13
[Ui] rated insulation voltage	690 V
[Uimp] rated impulse withstand voltage	6 kV
Utilisation category	AC-15 DC-13
Poles description	3P
Height	66 mm
Width	44 mm
Depth	96 mm
Product weight	0.2 kg

Environment

Installation category	III
Pollution degree	3
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-25...55 °C
Operating altitude	2000 m
Standards	IEC 60947-4-1
Product certifications	CB CE SEMKO

Relative humidity	0...95 %
-------------------	----------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Offer Sustainability

Sustainable packaging	No
-----------------------	----
