Nov 10, 2026

# Product data sheet

# HLAY5EA41

## Characteristics

**Push-button, HLAY5, flush, 1 NO, red**




### Main

| | |
|---|---|
| Range of product | HLAY5 |
| Device presentation | Complete product |
| Product or component type | Push-button |
| Bezel material | Plastic |
| Mounting diameter | 22 mm |
| Head type | Standard |

### Complementary

| | |
|---|---|
| Cap/operator or lens colour | Red |
| Fixing collar material | Plastic |
| Shape of signaling unit head | Round |
| Type of operator | Spring return |
| Operator profile | Red flush |
| Contacts type and composition | 1 NO |
| Contact operation | Slow-break |
| Contacts usage | Standard contacts |
| Mechanical durability | 1000000 cycles |
| Connections - terminals | Screw clamp terminals |
| [Ith] conventional free air thermal current | 6 A |
| [Uimp] rated impulse withstand voltage | 6 kV |
| [Ie] rated operational current | 2 A at 380 V<br>3.3 A at 220 V, AC-15<br>0.5 A at 220 V<br>1.1 A at 110 V, DC-13 |
| Electrical durability | 1000000 cycles AC<br>200000 cycles DC |
| E-commerce address | Hlay5-pushbuttons-mushroom-and-emergency-stop-pushbuttons-1 |

### Environment

| | |
|---|---|
| Ambient air temperature for operation | -5…40 °C |
| IP degree of protection | IP40<br>IP65 with protective cover |
| Standards | IEC 60947-5-1 |

### Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|---|---|
| Number of Units in Package 1 | 1 |

## Offer Sustainability

| | |
|---|---|
| Sustainable packaging | No |